

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 667 544 A1

(12)

EUROPEAN PATENT APPLICATION(21) Application number: **95102089.0**(51) Int. Cl.⁶: **G02B 6/38**(22) Date of filing: **15.02.95**

(30) Priority: **15.02.94 JP 18573/94**
15.02.94 JP 18566/94

(43) Date of publication of application:
16.08.95 Bulletin 95/33

(84) Designated Contracting States:
DE FR GB SE

(71) Applicant: **SUMITOMO ELECTRIC INDUSTRIES, LTD.**
5-33, Kitahama 4-chome,
Chuo-ku
Osaka-shi,
Osaka 541 (JP)

(72) Inventor: **Akita, Osamu, c/o Osaka Works of**
Sumitomo Elec. Ind., Ltd.,

1-3, Shimaya 1-chome
Konohana-ku,
Osaka-shi,
Osaka 554 (JP)


Inventor: **Nakanishi, Hiromi, c/o Osaka Works**
of
Sumitomo Elec. Ind., Ltd.,
1-3, Shimaya 1-chome
Konohana-ku,
Osaka-shi,
Osaka 554 (JP)

(74) Representative: **Füchsle, Klaus, Dipl.-Ing. et al**
Hoffmann, Eitle & Partner,
Patentanwälte,
Arabellastrasse 4
D-81925 München (DE)

(54) **Card-shaped optical data link device.**

(57) A card-shaped optical data link device is utilized for transmitting and receiving data in optical communications using an existing card slot of a computer, electronic devices etc. The card-shaped optical data link device of the present invention comprises an electric connector, electric signal processor 20 electrically connected to the electric connector, an optical transmission module 30, an optical reception module 30A electrically connected to the electric signal processor 20, an optical connector 50 for supporting the optical transmission module 30 and the optical reception module 30A, a frame 11 for supporting the electric connector and the optical connector 50 at a position opposing to the electric connector, and a pair of panels 12 for sandwiching the frame 11 and constituting an envelope with the frame 11. The electric connector, the electric signal processor, the optical transmission module 30, the optical reception module 30A and the optical connector 50 are located within the envelope.

F i g. 1



BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a card-shaped optical data link device to be utilized for transmitting and receiving data in optical communications using computers, electronic devices, or measurement devices.

Related Background Art

10 In recent years, networking to personalize information with facsimiles, personal computers etc. has come into wide use.

Recent demands are high information-oriented society that large data are readily transmitted and received in optical communications with high speed.

15 SUMMARY OF THE INVENTION

It is an object of the present invention to provide a card-shaped optical data link device to be utilized for transmitting and receiving data in optical communications using an existing card slot of a computer, electronic devices etc.

20 In order to achieve the object, a first type card-shaped optical data link device of the present invention comprises an electric connector for receiving and transmitting an electric signal from and to an external environment, electric signal processor electrically connected to the electric connector, an optical transmission module electrically connected to the electric signal processor, for converting the electric signal received from the electric signal processor into an optical signal, an optical reception module electrically
25 connected to the electric signal processor, for converting an optical signal into an electric signal, an optical connector for supporting the optical transmission module and the optical reception module, a frame for supporting the electric connector and the optical connector at a position opposing to the electric connector, and a pair of panels for sandwiching the frame and constituting an envelope with the frame, the envelope housing the electric connector, the electric signal processor, the optical transmission module, the optical
30 reception module and the optical connector, and the electric connector, the electric signal processor, the optical connector, the optical transmission module and the optical reception module are located within the envelope.

Alternatively, a second type card-shaped optical data link device comprises an electric connector for receiving and transmitting an electric signal from and to an external environment, electric signal processor
35 connected to the electric connector, an output socket electrically connected to the electric signal processor, a frame for supporting the electric connector and the optical connector at a position opposing to the electric connector, a pair of panels for sandwiching the frame and constituting an envelope with the frame, the envelope housing the electric connector, the electric signal processor and the output socket, a cable connected to the output socket to transmit an electric signal from and to the electric signal processor, an
40 optical transmission module for converting the electric signal received from the electric signal processor through the cable into an optical signal, an optical reception module for converting an optical signal into an electric signal and sending the electric signal to the electric signal processor through the cable, an optical connector for supporting the optical transmission module and the optical reception module, and a housing for storing the optical connector, the optical transmission module, and the optical reception module.

45 Alternatively, a third type card-shaped optical data link device comprises an electric connector for receiving and transmitting an electric signal from and to an external environment, electric signal processor electrically connected to the electric connector, an optical transmission module electrically connected to the electric signal processor, for converting the electric signal received from the electric signal processor into an optical signal, an optical reception module electrically connected to the electric signal processor, for
50 converting an optical signal into an electric signal, a transmission optical fiber having a first end fitted into the optical transmission module, a reception optical fiber having a first end fitted into the optical reception module, a frame for supporting the electric connector, and the optical transmission module and the optical reception module at a position opposing to the electric connector, and a pair of panels for sandwiching the frame and constituting an envelope with the frame, the envelope housing the electric connector, the electric
55 signal processor, the optical transmission module, and the optical reception module, and the electric connector, the electric signal processor, the optical transmission module and the optical reception module are located within the envelope.

According to the first type card-shaped optical data link device of the present invention, the card-shaped optical data link device is formed in card shape with the panel, frame and panel, so that the thickness of the card-shaped optical data link device is thin. Therefore, the card-shaped optical data link device is readily inserted into, e.g., an existing card slot of a computer to transmit data in optical communications.

Further, cuts may be formed on a surface to be covered with the panel to make the card-shaped optical data link device thin.

According to the second type card-shaped optical data link device, the portion which is to be inserted into, e.g., an existing card slot of a computer is made thin, and the housing for housing the optical transmission and reception modules is separately formed. Therefore, the second type card-shaped optical data link device can also be readily inserted into, e.g., an existing card slot of a computer to transmit data in optical communications.

According to the third type card-shaped optical data link device, the portion which is to be inserted into, e.g., an existing card slot of a computer is made thin, so that the third type card-shaped optical data link device can also be readily inserted into, e.g., an existing card slot of a computer to transmit data in optical communications. Further, the transmission optical fiber and the reception optical fiber are fitted hard into the optical transmission module and the optical reception module, respectively. Accordingly, another equipment to hold the optical fibers is not needed.

An existing card slot of a computer, for example, is conventionally used for communication cards which output and receive electric signals. The communication cards are standardized by JEIDA (Japanese Electronic Industry Development Association). In the guideline ver. 4.1 by JEIDA, there are type I and type II communication cards. Their standards are shown in Table 1.

TABLE 1

Type	Length	Width	Thickness	Body Thickness
I	85.6±0.2	54.0±0.1	3.3±0.1	3.3±0.2
II	85.6±0.2	54.0±0.1	3.3±0.1	below 5.0, t±0.2

[unit:mm]

In Table 1, t (arbitrary size) is a normal size of the body thickness of the card.

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not to be considered as limiting the present invention.

Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWING

Fig. 1 is a perspective view showing a first type card-shaped optical data link device according to the first embodiment of the present invention, with a connector plug being inserted.

Fig. 2 is a sectional view showing an optical connector of the card-shaped optical data link device of the first embodiment.

Fig. 3 is a top view showing the card-shaped optical data link device of the first embodiment.

Fig. 4 is a sectional view showing an electric connector of the card-shaped optical data link device of the first embodiment.

Figs. 5 and 6 are views showing a housing of the optical data link of the first embodiment.

Fig. 7 is a perspective view showing a card-shaped optical data link device being inserted into a computer.

Fig. 8 is a perspective view showing a card-shaped optical data link device being inserted into a slot of the computer.

Fig. 9 is a sectional view showing an optical transmission module and an optical reception optical module.

Fig. 10 is a top view showing a transmission connector plug and a reception connector plug of the card-shaped optical data link device.

Fig. 11 is a side view showing the transmission connector plug and the reception connector plug of the card-shaped optical data link device.

5 Fig. 12 is a side view showing the transmission connector plug and the reception connector plug of the card-shaped optical data link device with a protective cap.

Fig. 13 is a perspective view showing assembling of the optical connector and the optical transmission and reception modules of the card-shaped optical data link device of the first embodiment.

10 Fig. 14 is a perspective view showing a completed optical connector and the optical transmission and reception modules.

Fig. 15 is a side view showing an optical connector without a cut.

Fig. 16 is a side view showing an optical connector with a cut.

Figs. 17, 18 and 19 are views showing another optical connector of the card-shaped optical data link device according to the first embodiment of the present invention.

15 Fig. 20 is a side view showing an optical connector with cuts.

Fig. 21 is a perspective view showing a first type card-shaped optical data link device of the second embodiment.

Fig. 22 is a side view showing an optical connector of the first type card-shaped optical data link device of the second embodiment.

20 Fig. 23 is a top view showing the first type card-shaped optical data link device of the second embodiment.

Fig. 24 is a sectional view showing another optical connector with an optical module being inserted.

Fig. 25 is a perspective view showing a second type card-shaped optical data link device according to the third embodiment of the present invention.

25 Fig. 26 is a top view showing the second type card-shaped optical data link device.

Fig. 27 is a side view showing an optical connector of the second type card-shaped optical data link device of the third embodiment.

Fig. 28 is a top view showing the optical connector and a cable of the card-shaped optical data link device of the third embodiment.

30 Fig. 29 is a sectional view showing another optical transmission module and optical reception module of the card-shaped optical data link device of the third embodiment.

Figs. 30 and 31 are views showing a second type card-shaped optical data link device according to the fourth embodiment.

35 Fig. 32 is a top view showing an optical connector and optical transmission and reception modules of the second type card-shaped optical data link device according to the fifth embodiment.

Fig. 33 is a perspective view showing a third type card-shaped optical data link device according to the sixth embodiment of the present invention.

Fig. 34 is a sectional view of an optical fiber used in the third type card-shaped optical data link device.

Fig. 35 is a view showing a card-shaped optical data link device connection.

40 Fig. 36 is a sectional view showing an optical fiber of the third type card-shaped optical data link device being coupled to another optical fiber.

Fig. 37 is a top view showing a third type card-shaped optical data link device.

Fig. 38 is a sectional view showing the optical fiber being inserted into the optical module.

45 Fig. 39 is a sectional view showing an optical connector plug and an optical module of the third type card-shaped optical data link device according to the seventh embodiment.

Fig. 40 is a perspective showing another optical connector plug.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

50 The embodiments of the present invention will be described with reference to the accompanying drawings. The same components are represented by the same reference numerals and the repetitive description on the same components is omitted.

Fig. 1 shows a first type card-shaped optical data link device of the first embodiment. As shown in Fig. 1, there are an electric circuit board 20, an optical transmission module, an optical reception module 30A and an optical connector 50, in a housing 10. An MU-optical transmission connector plug 41 having a transmission optical fiber 40 is fitted into the optical connector 50 so that the optical transmission module is optically coupled with the transmission optical fiber 40, and an MU-optical reception connector plug 41A having a reception optical fiber 40A is fitted into the optical connector 50 so that the optical reception

module 30A is optically coupled with the reception optical fiber 40A.

The housing 10 comprises a flat rectangular frame 11 and metal panels 12 sandwiching the frame 11. The housing 10 is formed thin in conformity with the type II communication card. This is because the type II communication card is superior in processability since it is thicker than the type I communication card. The frame 11, as shown in Figs. 2 through 6, is a flat rectangular frame with one open side and has an attaching space 13 at a center of a short side to fix the optical connector 50. The frame 11 supports the electric connector 22 at another short side. Fig. 5 shows one example of the frame 11. When the optical connector 50 is fixed at the attaching space 13 of the frame 11 shown in Fig. 5, the optical transmission and reception modules 30 and 30A are inserted into respective holes 7 of the frame 11 from the electric connector side and inserted into the optical connector 50. The thin flat rectangular metal panels 12, as shown in Fig. 1, sandwich the frame 11 to efficiently protect and shield the electronic circuit board 20, the electric connector 22, the optical transmission module 30, the optical reception module 30A, and the optical connector 50. Accordingly, the housing 10 is formed in conformity with the type II communication card which has the length of 85.6 ± 0.2 mm, the width of 54.0 ± 0.1 mm, the coupling portion thickness of 3.3 ± 0.1 , and the body thickness of 5.0 mm or below.

In the first embodiment, the metal panels 12 efficiently protect and shield the electronic circuit board 20, the electric connector 22, the optical transmission module 30, the optical reception module 30A and the optical connector 50 but the metal panels 12 may protect and shield the whole portion or a part of the electronic circuit board 20, the electric connector 22, the optical transmission module 30, the optical reception module 30A and the optical connector 50. Further, the panels 12 may be formed with engineering plastic or another material if the material shows the same functions and effects. Furthermore, in the first embodiment, the housing 10 is formed in conformity with the type II communication card but it may be formed in conformity with the type I communication card, which also shows the same functions and effects.

The electronic circuit board (electric signal processor) 20 is formed thin, flat rectangular. ICs with plurality of pins are mounted on the surface of the electronic circuit board 20 which is housed in the housing 10. The electric connector 22 which is a female connector as shown in Fig. 4 is placed at one short side of the electronic circuit board 20.

As shown in Fig. 7, the card-shaped optical data link device is inserted into a card slot 210 of a computer 200 to transmit data between the computer 200 and external devices. Fig. 8 shows the card-shaped optical data link device being inserted into the card slot 210. There is a frame 211 for guiding the card-shaped optical data link device inside the card slot 210. As the card-shaped optical data link device is inserted into the card slot 210, it moves on the frame 211 to the inside of the slot 210 and the electric connector 22 is connected with pins 212 and rests on the board 213. Then, the data are transmitted between the card-shaped optical data link device and the computer 200 through a cable 214. The electronic circuit board 20 has a function to process electric signals transmitted with the computer 200 upon the connection of the electric connector 22 and the pins 212.

In this embodiment, the electronic circuit board 20 shown in Fig. 3 is used but it is not limited to this structure and shape if it shows the same functions and effects. Further, in the present embodiment, the optical communication means is a computer but it is apparent that another devices can be used if they can be used in optical communications, for example, facsimiles, measuring apparatus, optical devices, electrical communication device etc.

Fig. 9 shows the optical transmission module 30 utilized in the present embodiment. As shown in Fig. 9, the optical transmission module 30 has a cylindrical sleeve 32 with both ends open and a main body having two flat surfaces. The main body is fixed on a backside of a substantially circular device package 31. The optical transmission module 30 is housed in the housing 10 and connected to the electric connector with a wire 19. The optical transmission module 30 has a function to convert an electric signal transmitted from the electronic circuit board 20 into an optical signal and to transmit the optical signal to the external device. There are plural lead pins 33 formed on the front side of the device package 31, and the lead pins 33 are electrically connected to the electronic circuit board 20 through wires 19. An LED for converting an electric signal into an optical signal, or an optical device 34 such as an LD, as well as a cap 35, is mounted on the center portion of the backside of the device package 31. The cap 35 has a lens 36 fixed at the center which is to optically couple the optical device 34 with the optical transmission fiber 40 supported by a ferrule 42 which is described later when the ferrule 42 is inserted into the module 30. A precision sleeve 37 for accurately supporting the ferrule 42 having the transmission optical fiber 40 is formed with high accuracy at the inner surface of the sleeve 32. Also, there are claws 38 for stopping the ferrule 42 at the inner surface of the sleeve 32. When the ferrule 42 is inserted into the sleeve 37 of the optical reception module 30, the optical fiber 40 supported by the ferrule 42 receives light emitted from the optical device 34 through the lens 36.

It should be noted that in this embodiment, the optical reception module 30 shown in Fig. 9 is used but it is not limited to this structure and shape if it has the same function. Further, it is apparent that the sleeve 32 shown in Fig. 9 can be replaced, e.g., with a sleeve having a slit in an extending direction.

Fig. 10 shows a connector plug utilized in the present embodiment, and Fig. 11 shows a front view of the connector plug, and Fig. 12 shows a side view of the connector plug. As shown in Fig. 10, the transmission optical fiber 40 is coated with a coating layer to be protected, and an MU-optical transmission connector plug 41 is fitted on the tip of the optical fiber 40. The MU-optical transmission connector plug 41 is integrally formed with the Mu-optical reception connector plug 41A by its side. The cylindrical ferrule 42 is fitted on the tip of the transmission optical fiber 40. When this ferrule 42 is inserted into the precision sleeve 37, the ferrule 42 prevents the imperfect alignment of the transmission optical fiber 40. The MU-transmission optical connector plug 41 utilized in the present embodiment is formed 4.4mm thick while the conventional FDDI-, SC-, FC-, and ST-transmission optical connector plugs are formed 5mm thick or above. The optical connector plug 41 is a receptacle type plug which is removable, and its shape is an elongated prism. The MU-optical connector plug is superior in small size, light weight, high performance, high reliability, low cost, which has been widely used. The MU-transmission optical connector plug 41 is used in the present embodiment because it is able to be inserted into the optical connector 50 of the housing 10 without hinderance owing to its 4.4 mm thickness.

It should be noted that the transmission optical fiber 40 is used in the present embodiment but any kinds of transmission optical fibers may be used if the fiber has a function of transmitting light. The optical transmission connector plug 41 is not limited to the MU-connector plug but other kinds of optical transmission connector plug 41 may be used. For example, Product No. HMUA-P2-H1, No. HMUA-P2-H2, No. HMUA-2P2-H1, No. HMUA-2P2-H2, product of HIROSE DENKI may be used.

The optical reception module 30A has the same configuration as the optical transmission module 30 shown in Fig. 9 except that the optical device 34 is a pin photodiode for receiving light. When the ferrule 42 is inserted into the sleeve 37 of the optical reception module 30A, the optical device 34 receives light emerging from the optical fiber 40A supported by the ferrule 42.

It should be noted that, in this embodiment, the optical reception module 30A shown in Fig. 9 is used but it is not limited to this structure and shape if it has the same function. Further, it is apparent that the sleeve 32 shown in Fig. 9 can be replaced, e.g., with a sleeve having a slit in an extending direction.

As shown in Fig. 10, the reception optical fiber 40A is coated with a coating layer to be protected, and an MU-optical reception connector plug 41A is fitted on the tip of the optical fiber 40A. The MU-optical reception connector plug 41A is integrally formed with the Mu-optical reception connector plug 41 by its side. The cylindrical ferrule 42 is fitted on the tip of the reception optical fiber 40A. When this ferrule 42 is inserted into the precision sleeve 37, the ferrule 42 prevents the imperfect alignment of the reception optical fiber 40A. The MU-reception optical connector plug 41A utilized in the present embodiment is formed 4.4mm thick while the conventional FDDI-, SC-, FC-, and ST-reception optical connector plugs are formed 5mm thick or above. Also, the optical connector plug 41A is a receptacle type plug which is removable, and its shape is an elongated prism. The MU-optical connector plug is superior in small size, light weight, high performance, high reliability, low cost, which has been widely used. The MU-reception optical connector plug 41A is used in the present embodiment because it is able to be inserted into the optical connector 50 of the housing 10 without hinderance owing to its 4.4 mm thickness.

It should be noted that the reception optical fiber 40A is used in the present embodiment but any kinds of reception optical fibers may be used if the fiber has a function of transmitting light. The optical reception connector plug 41A is not limited to the MU-connector plug but other kinds of optical reception connector plug 41 may be used. For example, Product No. HMUA-P2-H1, No. HMUA-P2-H2, No. HMUA-2P2-H1, No. HMUA-2P2-H2, product of HIROSE DENKI may be used. Reference numeral 42A shown in Fig. 12 is a protective cap for protecting the tips of the connector plugs 41 and 41A.

The optical connector 50 made of engineering plastic has a box shape with an open front side, as shown in Figs. 2 and 3 and Figs. 13 and 14. The optical connector 50 together with a block 60 made of A1 or plastic is fitted in the attaching space 13 formed in the frame 11 and housed and protected in the housing 10. The optical connector 50 supports the optical transmission module 30 and the optical reception module 30A horizontally, and the MU-optical transmission connector plug 41 and the MU-optical transmission connector plug 41A are inserted into the optical connector 50. There is a division plate 51 integrally molded in the middle of the optical connector 50 to divide the internal space into two adaptor spaces. Also, there are a pair of holes (not shown) at the back side of the optical connector 50 horizontally. The sleeves 32 of the optical transmission and reception modules 30, 30A are inserted into the respective holes. There are also one pair of holding strips 52 projecting to the front side of the optical connector 50 in each adaptor space of the optical connector 50. These two pairs of the holding strips 52 latch the optical connector plugs

41 and 41A when the optical connector plugs 41 and 41A are fitted into the optical connector 50. Cuts 53 are formed on the upper surface (surface to be covered with the panel 12) of the optical connector 50 from the front side to the back side. These cuts 53 contribute to making the thin optical connector.

Fig. 15 shows the cross section of the optical connector without a cut and Fig. 16 shows the cross section of the optical connector with a cut. The optical connector 50 has a box shape so as to surround the MU-optical transmission connector plug 41 and the optical reception connector plug 41A when they are inserted therein. The optical connector 50 needs to protect these plugs, so that the thickness of the upper surface and the lower surface needs at least 0.3 mm in a view of mechanical integrity.

The thickness T4 of the optical connector without the cut shown in Fig. 15 is the thickness of the space for the optical connector plug which is equal to the thickness of the plug 41 or 41A, 4.4mm + the thickness of the lower surface 50a, 0.3mm + the thickness of the upper surface 50b, 0.3mm + the thickness of one pair of the metal panels 12, $0.15\text{mm} \times 2 = 5.3\text{mm}$. On the other hand, the thickness T3 of the optical connector with the cut shown in Fig. 16 is the thickness of the space for the plug, 4.4 mm + the thickness of the lower surface 50a, 0.3mm + the thickness of the metal panels 12, $0.15\text{mm} \times 2 = 5.0\text{mm}$. As apparent from these figures, the optical connector 50 with a cut is thinner than the optical connector 50 without a cut, and it is suitable for the card-shaped optical data link device formed in conformity with the type II communication card. In the optical connector with a cut, the upper surface of the optical connector also has 0.3mm in thickness, so that the optical connector with cut sufficiently protects the plugs 41, 41A.

The optical reception module 30A and the optical transmission module 30 have the shape shown in Fig. 13 that the sleeve 32 is cylindrical and the main body has the flat upper surface 39a and the flat lower surface 39b.

The block 60 shown in Figs. 13 and 14 is formed substantially U-shape and made of metal, plastic etc. The block 60 is placed in the attaching spacing 13 of the frame 11, e.g., with an adhesive. The optical connector 50 is fixed in the block 60 by laser welding or an adhesive. The block 60 has one pair of holes 61 at the back surface which is to be attached to the back surface of the optical connector 50. The sleeves 32 of the optical transmission and reception modules 30 and 30A are inserted into the respective holes 61. As shown in Fig. 13, the thickness T2 of the block 60 is substantially the same as the thickness T3 of the optical connector 50, and the thickness T1 of the main body of the optical module 30 between the two flat surfaces 39a, 39b is less than or equal to the thickness T3 of the connector 50. The thickness T3 of the connector 50 is less than or equal to the thickness of the frame 11.

In the present embodiment, the optical connector 50 shown in Figs. 2 and 3 or Figs. 13 and 14 is used, but another optical connector having the different shape and configuration, e.g., shown in Figs. 17-19, may be used therefor if it has the same function and effect. Fig. 17 shows a top view of the optical connector, and Fig. 18 shows a front view of the optical connector, and Fig. 19 shows a side view of the optical connector. As shown in Figs. 17 to 19, a pair of holding stripes 52 are formed on the internal side walls of the optical connector 50. Further, also in the present embodiment, the block 60 and the optical connector 50 are formed separately but the block 60 may be integrally molded with the optical connector 50, which also shows the same function and effect. Furthermore, cuts may also be formed on the lower surface of the optical connector 50 as shown in Fig. 20 from the front side to the back side in addition to the cuts on the upper surface. The thickness T5 of the optical connector 50 with cuts on both upper and lower surfaces shown in Fig. 20 is the thickness of the space for the optical connector plug which is equal to the thickness of the plug 41 or 41A, 4.4mm + the thickness of one pair of the metal panels 12, $0.15\text{mm} \times 2 = 4.7\text{mm}$. The thickness of the optical connector 50 with cuts on both upper and lower surfaces is thinner than that of the optical connector 50 with the cuts on the upper surface, so that with the use of the optical connector 50 with the cuts on both upper and lower surfaces, the card-shaped optical data link device can be made 4.7mm thick. In this case, the upper and lower surfaces of the optical connector 50 also have 0.3mm in thickness, so that the optical connector 50 with cuts on both upper and lower surfaces sufficiently protects the plugs 41, 41A.

The card-shaped optical data link device with the above-described configuration is inserted into the card slot 210 of the personal computer 200 as shown in Fig. 7, and the optical transmission and reception connector plugs 41 and 41A are fitted into the optical connector 50 when data are transmitted between the computer and the external device in optical communications.

When the data are transmitted from the computer 200 to the external device in optical communications, an electric signal is sent from the computer 200 to the electronic circuit board 20 through the electric connector 22, and the electronic circuit board 20 processes the electric signal. The processed electric signal is sent to the optical transmission module 30. Then, the optical device 34 such as an LED converts the electric signal into the optical signal, and the optical signal is transmitted to the external device through the transmission optical fiber 40.

On the other hand, when the data are received from the external device, an optical signal is sent from the external device to the optical reception module 30A through the reception optical fiber 40A. Then, the optical device 34 such as a pin photodiode of the optical reception module 30A converts the optical signal into the electric signal and the electric signal is sent to the electronic circuit board 20. The electronic circuit board 20 processes the electric signal, and the processed electric signal is sent to the computer through the electric connector 22 which is connected to the pins 212 in the slot 210 of the computer 200.

According to the above-described configuration of the card-shaped optical data link device, the housing 10 is formed thin in conformity with the type II communication card standardized by JEIDA, so that the existing card slot of the computer, for example, can be used to transmit and receive data in optical communication. Further, the optical connector 50 has the cuts 53 on the upper surface thereof from the front side to the back side, which makes the optical connector 50 thin. Consequently, the thickness of the optical connector 50 is made 5mm or below. Furthermore, the optical connector 50, the optical transmission module 30 and the optical reception module 30A are all stored in the housing 10, so that the reduction of the number of parts, the improvement of the work efficiency upon the installation and the reduction of the size accuracy of the parts are attained, compared with the case of assembling separate parts.

Further, the card-shaped optical data link device is expected to be utilized in LAN. The frame 11 are sandwiched between the metal panels 12, so that the electronic circuit board 20, the electric connector 22, the optical transmission module 30, the optical reception module 30A and the optical connector 50 are efficiently protected and shield from the external environment. The precision sleeves 37 are formed at the sleeves 32 of the optical transmission module 30 and the optical reception module 30A, which largely suppress optical losses. Since the thickness of the optical transmission connector plug 41 and the optical reception connector plug 41A is 4.4 mm, they are readily fitted into the optical connector 50 to transmit and receive data in optical communications. The optical connector 50 holds the optical transmission module 30 and the optical reception module 30A horizontally, which means the optical transmission module 30 is placed by the side of the optical reception module 30A in the direction of the short side of the frame 11, so that the housing 10 will not be thick. Since the pairs of the holding strips 52 latch the optical connector plugs 41, 41A, the imperfect alignment of the optical transmission and reception modules 30 and 30A with the transmission and reception optical fibers 40 and 40A which are supported by the optical connector plugs 41 and 41A is prevented.

Next, the second embodiment of the card-shaped optical data link device which belongs to the first type card-shaped optical data link device will be described.

Fig. 21 shows a perspective view of the card-shaped optical data link device of the second embodiment, and Fig. 22 shows a front view of an optical connector of the card-shaped optical data link device, and Fig. 23 shows a top view of the card-shaped optical data link device. The card-shaped optical data link device of the second embodiment is different from the card-shaped optical data link device of the first embodiment in that the frame 11A and the optical connector 50A are integrally molded from a plastic such as PPS, PES and a liquid crystal polymer.

The integrally formed optical connector 50A has a pair of holes 54 horizontally to which an optical transmission module 30 and an optical reception module 30A are inserted. As shown in Fig. 24, the optical module 30 or 30A is inserted into the hole 54. There are a pair of holding stripes 52 for latching the optical connector plug 41 or 41A when they are fitted into the optical connector 50A.

The engineering plastic is used in molding of the housing 10A and the optical connector 50A. This is because the engineering plastic is superior in heat resistance and in mechanical integrity. The remaining portions have the same configurations as in the first embodiment.

Also in the second embodiment, the same function and effect as in the first embodiment are attained. The optical transmission and reception modules 30 and 30A in which the optical device 34 and the sleeve 32 are aligned and assembled beforehand are horizontally inserted into the holes 54 of the frame 11A which constitutes the housing 10A, so that the reduction of the processing steps is attained.

Next, the card-shaped optical data link device according to the third embodiment of the present invention will be described with reference to Figs. 25 to 29. The card-shaped optical data link device of the third embodiment belongs to the second type card-shaped optical data link device of the present invention.

Fig. 25 shows a perspective view of the card-shaped optical data link device and Fig. 26 shows a top view thereof. The card-shaped optical data link device of the third embodiment as shown in Figs. 25 and 26 comprises a housing 100 which contains an electronic circuit board 20, an output socket 23, a cable 65 with a connector 66 to be connected to the output socket 23, and an optical connector 70 containing an optical transmission module 30 and an optical reception module 30A, to be connected to the cable 65.

The housing 100 comprises a flat rectangular frame 110 and metal panels (panel) 120 sandwiching the frame 110, which is formed thin in conformity with the type II communication card standardized by JEIDA.

The frame 110, as shown in Fig. 26, is a flat rectangular frame with one open side and has an attaching space 14 at a center of a short side to fix the connector 66 of the cable 65. The frame 110 supports the electrical connector 22 at another short side which is the open end. The thin flat rectangular metal panels 120, as shown in Fig. 25, sandwich the frame 110 to efficiently protect and shield the electronic circuit board 20, the electrical connector 22, and the output socket 23. Accordingly, the housing 100 is formed in conformity with the type II communication card which has the length of 85.6 ± 0.2 mm, the width of 54.0 ± 0.1 mm, the coupling portion thickness of 3.3 ± 0.1 , and the body thickness of 5.0 mm or below.

In the third embodiment, the metal panels 120 efficiently protect and shield the electronic circuit board 20, the electric connector 22 and the output socket 23 but the metal panels 120 may protect and shield the whole portion or a part of the electronic circuit board 20, the electric connector 22, and the output socket 23. Further, the panels 120 may be formed with plastic or another material if the material shows the same functions and effects. Furthermore, in the third embodiment, the housing 100 is formed in conformity with the type II communication card but it may be formed in conformity with the type I communication card, which also shows the same functions and effects.

The electronic circuit board (electric signal processor) 20 is formed thin, flat rectangular. ICs with plurality of pins are mounted on the surface of the electronic circuit board 20 which is housed in the housing 100. The electric connector 22 standardized by JEIDA is fixed at the end of the electronic circuit board 20, located at the short side of the frame 110. The electric connector 22 has the same configuration as in the first embodiment and it is utilized in the same way as in the first embodiment. The output socket 23 located at the attaching space 14 of the frame 110 is connected to the middle of the short side end of the electronic circuit board 20. The electronic circuit board 20 has a function to process an electric signal when the electric connector 22 is connected to the external device such as a computer.

In this embodiment, the electronic circuit board 20 shown in Fig. 26 is used but it is not limited to this structure and shape if it shows the same functions and effects.

The optical transmission module 30, the optical reception module 30A, the transmission optical fiber 40, and the reception optical fiber 40A in the present embodiment are the same as those used in the first embodiment. The optical transmission connector plug 41 and the optical reception connector plug 41A to be connected to the optical connector 70 are also the same as those used in the first embodiment.

It should be noted that in this embodiment, the optical transmission and reception modules 30, 30A shown in Fig. 9 are used but they are not limited to this structure and shape if they have the same function. For example, an optical module shown in Fig. 29 may be used. Alternatively, the optical module having a cylindrical main body may be used. Further, it is apparent that the sleeve 32 shown in Fig. 29 can be replaced, e.g., with a sleeve having a slit in an extending direction.

It should also be noted that the transmission and reception optical fibers 40, 40A are used in the present embodiment but any kinds of transmission optical fibers may be used if the fiber has a function of transmitting light. The optical transmission and reception connector plugs 41, 41A are not limited to the MU-connector plugs but other kinds of optical transmission and reception connector plugs 41, 41A, e.g., FDDI-, SC-, FC-, and ST-connector plugs, may be used.

The optical connector 70 made of plastic has a box shape with an open front side, as shown in Figs. 25 to 28. The optical connector 70 holds the optical transmission module 30 and the optical reception module 30A horizontally, and the MU-optical transmission connector plug 41 and the MU-optical reception connector plug 41A are inserted into the optical connector 70. There is a partition plate 74 in the middle of the optical connector 70 to divide the internal space into two adaptor spaces. The partition plate 71 has a pair of holes to which the optical transmission and reception modules 30 and 30A are inserted. There is a division plate 71 integrally molded with the partition plate 74 to further divide the internal space of one adaptor space divided by the partition plate 74 into two adaptor spaces. There are also one pair of holding strips 72 projecting to the front side of the optical connector 70 in each adaptor space divided by the division plate 71 of the optical connector 70, as shown in Fig. 26 and Fig. 28. These two pairs of the holding strips 72 latch the optical connector plugs 41 and 41A. Cuts 73 are formed on the upper surface of the optical connector 70 from the front side to the back side. These cuts 73 contribute to making the thin optical connector and function to hold the protruding portion (tab) of the MU-optical transmission and reception connector plugs (note that connector plugs 41 and 41A shown in Fig. 40 which will be described later do not have a protrusion portion.)

In the present embodiment, the optical connector 70 has the cuts but the cuts are not required if the optical transmission connector plug 41 and the optical reception connector plug 41A do not have the protrusion portions or if the optical connector 70 does not have to be formed thin. The optical connector 70 may be changed in accordance with the kinds of the optical transmission and reception connector plugs 41 and 41A such as FDDI-, SC-, FC-, or ST-connector plugs. The thickness of the optical connector 70 may be

formed 5mm or above. This is because only the housing 100 containing the electric board 20 is inserted into, e.g., the card slot of the computer, so that the optical connector 70 does not have to be thin. For the same reason, the size of the optical transmission and reception modules 30, 30A located in the optical connector 70 is not limited.

The cable 65 has the connector 66 attached with pins 67. The pins 67 are connected to the output socket 23 electrically connected to the electronic circuit board 20. The cable 65 has a protective hood 63 at the opposite side of the connector 66. Lead pins 33 of the optical transmission and reception modules 30 and 30A are coupled to the cable 65 with lead wires 64. Thus, the cable 65 has a function to electrically couple the electronic circuit board 20 with the optical transmission and reception modules 30 and 30A in the optical connector 70.

It should be noted that the pins 67 are removable from the output socket 23 in the present embodiment but the pins 67 may be fixed to the output socket 23 so as not to be removed from the socket 23.

The housing 100 of the card-shaped optical data link device with the above-described configuration is inserted into the card slot 210 of the personal computer 200 as shown in Fig. 7, and the optical transmission and reception connector plugs 41 and 41A are fitted into the optical connector 70 when data are transmitted between the computer and the external device in optical communications.

When the data are transmitted from the computer to the external device in optical communications, an electric signal is sent from the computer 200 to the electronic circuit board 20 through the electric connector 22, and the electronic circuit board 20 processes the electric signal. The processed electric signal is sent to the optical transmission module 30 successively through the output socket 23, the pins 67 and the cable 65. Then, the optical device 34 such as an LED converts the electric signal into the optical signal, and the optical signal is transmitted to the external device through the transmission optical fiber 40.

On the other hand, when the data are received from the external device, an optical signal is sent from the external device to the optical reception module 30A through the reception optical fiber 40A. Then, the optical device 34 such as a pin photodiode of the optical reception module 30A converts the optical signal into the electric signal and the electric signal is sent to the electronic circuit board 20 successively through the cable 65, the connector 66, the pins 67 and the output socket 23. The electronic circuit board 20 processes the electric signal, and the processed electric signal is sent to the computer through the electric connector 22.

According to the above-described configuration of the card-shaped optical data link device, the housing 100 is formed thin in conformity with the type II communication card standardized by JEIDA, so that the existing card slot of the computer, for example, can be used to transmit and receive data in optical communications. Since the housing 100 and the optical connector 70 are formed separately, the optical connector 70 does not have to be formed thin. It may be formed 5mm thick or above, and the existing optical transmission and reception connector plugs 41 and 41A such as FDDI-, SC-, FC-, or ST-connector plugs which have the thickness of 5mm or above may be used.

Further, the frame 110 are sandwiched between the metal panels 120, so that the electronic circuit board 20, the electric connector 22, the output socket 23 and the pins 67 are efficiently protected and shield from the external environment. The precision sleeves 37 are formed at the sleeves 32 of the optical transmission module 30 and the optical reception module 30A, which largely suppress optical losses. Furthermore, the pairs of the holding stripes 72 latch the optical connector plugs 41 and 41A when they are inserted into the optical connector 70. Further, the optical connector 70 has the cuts 73 on the upper surface thereof from the front side to the back side, which makes the optical connector 70 thin.

Next, the card-shaped optical data link device of the fourth embodiment according to the present invention will be described. The card-shaped optical data link device of the present embodiment belongs to the second type card-shaped optical data link device. Fig. 30 and Fig. 31 show an optical connector, an optical transmission module and an optical reception module of the second type card-shaped optical data link device of the present embodiment. The card-shaped optical data link device of the fourth embodiment is different from the optical data link of the third embodiment in that a small drive circuit board 90 for driving the optical transmission and reception modules 30 and 30A is included in the optical connector 70. Accordingly, the optical transmission and reception modules 30 and 30A, and the drive circuit board 90 constitute one optical data link device. The cable 65 is connected to the drive circuit board 90 with lead wires 64. The remaining portions of the card-shaped optical data link device are as same as in the third embodiment.

This optical data link device of the present embodiment is connected to the housing 100 as the pins 67 of the cable 65 is connected to the output socket 23. The optical transmission and reception connector plugs are inserted into the optical connector 70 to be optically coupled with the optical transmission and reception modules 30 and 30A.

The housing 100 comprising the electronic circuit board 20 of the card-shaped optical data link device with the above-described configuration is inserted into the card slot 210 of the personal computer as shown in Fig. 7 when data are transmitted between the computer and the external device in optical communications.

When the data are transmitted from the computer to the external device in optical communications, an electric signal is sent from the computer 200 to the electronic circuit board 20 through the electric connector 22, and the electronic circuit board 20 processes the electric signal. The processed electric signal is sent to the drive circuit board 90 successively through the pins 67, the output socket 23, and the cable 65. Then, the drive circuit board 90 drives the optical transmission module 30 and the optical device 34 such as an LED converts the electric signal into the optical signal, and the optical signal is transmitted to the external device through the transmission optical fiber 40.

On the other hand, when the data are received from the external device, an optical signal is sent from the external device to the optical reception module 30A through the reception optical fiber 40A. Then, the optical device 34 such as a pin photodiode of the optical reception module 30A converts the optical signal into the electric signal and the electric signal is sent to the electronic circuit board 20 successively through the cable 65, the connector 66, the pins 67 and the output socket 23. The electronic circuit board 20 processes the electric signal, and the processed electric signal is sent to the computer through the electric connector 22.

Next, the card-shaped optical data link device of the fifth embodiment will be described, referring to Fig. 32. In Fig. 32, only the optical connector is shown because the remaining portions are the same as in the third embodiment.

The optical connector of the fifth embodiment is different from the optical connector of the third embodiment in that the optical connector 70 is spread into two parts, and the optical transmission module 30 and the optical reception module 30A are held in each part. Each module is connected to the cable 65 with lead wires 64.

Also in the present embodiment, the same function and effect are attained as in the above-described embodiments.

Next, the card-shaped optical data link device of the sixth embodiment, which belongs to the third type card-shaped optical data link device of the present invention will be described with reference to Figs. 33 to 38.

Fig. 33 shows the perspective view of the card-shaped optical data link device of the sixth embodiment, and Fig. 37 shows its top view. As shown in Fig. 33 and Fig. 37, the card-shaped optical data link device comprises a housing 101 containing an electronic circuit board 20 and an optical transmission module 30 and an optical reception module 30A which are fitted into a pair of attaching holes 13A, a transmission optical fiber 40 and a reception optical fiber 40A connected to the optical transmission module 30 and the optical reception module 30A, and connectors 80 and 80A which are fitted on the ends of the transmission optical fiber 40 and the reception optical fiber 40A. Another optical fibers are coupled to the transmission and reception optical fibers 40 and 40A through the connectors 80 and 80A.

The housing 101 comprises a flat rectangular frame 111 and metal panels 121 sandwiching the frame 111. The housing 101 is formed thin in conformity with the type II communication card. The frame 111, as shown in Figs. 33 and 37, is a flat rectangular frame with one open side and has a pair of attaching holes 13A at a center of a short side. The optical transmission module 30 and the optical reception module 30A are fitted into the attaching holes 13A shown as dotted line in Fig. 33, which form the pig-tail portion (connection). The pig-tail connection is disclosed in Japanese Utility Model Laid-Open No. HEI 1-136908 (136908/1989).

The attaching hole 13A, as shown in Fig. 38, has a largest diameter portion 13a to which the optical transmission module 30 or the optical reception module 30A is inserted, a large diameter portion 13b which is continuously formed with the largest diameter portion 13a and to which the ferrule 42 is inserted, and a small diameter portion 13c which is continuously formed with the large diameter portion 13b and which stops (holds) and positions the end portions of the ferrule 42. The remaining portions of the housing 101 are the same as in the first embodiment.

The electronic circuit board (electric signal processing means) 20 is formed thin, flat rectangular. ICs with plurality of pins are mounted on the surface of the electronic circuit board 20 which is housed in the housing 101. The electric connector 22 is connected to one short side of the electronic circuit board 20.

In the same way as in the first embodiment shown in Fig. 7, the housing 101 of the card-shaped optical data link device is inserted into a card slot 210 of a computer 200 to transmit data between the computer 200 and external devices. The data are transmitted with the optical fibers 40 and 40A extending from the housing 101. Fig. 34 shows the cross section of the optical fiber 40 taken in lines X-X in Fig. 33. The optical

fiber 40 has a core 81a and a cladding 81b surrounding the core 81a, and the core 81a and the cladding 81b are surrounded by a coating layer 82. The optical fiber 40A has the same configuration as the optical fiber 40.

Fig. 35 shows one way of using the card-shaped optical data link device in optical communications. In Fig. 35, another optical fiber 89 is optically coupled with the optical fiber 40 as the connector 80 fitted on the end of the optical fiber 40 and a connector 85 fitted on the end of the optical fiber 89 are inserted into an adaptor 88. Also, another optical fiber 89A is optically coupled with the optical fiber 40A as the connector 80A fitted on the end of the optical fiber 40A and a connector 85A fitted on the end of the optical fiber 89A are inserted into an adaptor 88A. Optical fibers 43 are used in room wiring. The optical fibers 89 and 89A are coupled to an optical branching device 44, and optical fibers 43 extend from the optical branching device 44 to the other optical branching device 45 and to another device (not shown).

Fig. 36 shows the cross section of the coupling of the optical fiber 40 with the optical fiber 89. As shown in Fig. 36, the connector 80 fitted on the end of the optical fiber 40 has a ferrule 83 at its end to support the optical fiber 40. Also the other connector 85 fitted on the end of the optical fiber 89 has a ferrule 86 at its end to support the optical fiber 89. The coupling of the optical fiber 40 with the optical fiber 89 is made as the optical connectors 80 and 85 are inserted from both sides of the adaptor 88. There is a sleeve portion 84 in the adaptor 88 and this sleeve portion 84 limits the outer diameter of the ferrules 83 and 86. The ferrule 83 is faced to the ferrule 86 in the sleeve portion 84, and optical axes of the optical fibers 40 and 89 are aligned. Since the sleeve portion 84 is formed with high accuracy, the loss due to coupling is very low. In the same way as above, the optical fiber 40A is optically coupled with the optical fiber 89A.

The optical transmission module 30 utilized in the present embodiment is shown in Fig. 38. As shown in Fig. 38, a sleeve 32 with both ends open is cylindrical, and one side of the sleeve 32 has a larger inner diameter than the other side. The portion with the large inner diameter of the sleeve 32 is fixed on a backside of a substantially circular device package 31, and fitted into the attaching hole 13A of the housing 101. The optical transmission module 30 converts an electric signal sent from the electronic circuit board 20 into an optical signal and transmits the optical signal to the outside through the transmission optical fiber 40. There are plural lead pins 33 formed on the front side of the device package 31, and the lead pins 33 are electrically connected to the electronic circuit board 20 through wires (not shown). An LED for converting an electric signal into an optical signal, or an optical device 34 such as an LD is mounted on the center portion of the backside of the device package 31. There is a lens 36 for optically coupling the optical device 34 with the transmission optical fiber 40. When the ferrule 42 is inserted into the sleeve 32 of the optical reception module 30, the optical fiber 40 supported by the ferrule 42 receives light emitted from the optical device 34 through the lens 36. The remaining portions are the same as the optical transmission module 30 utilized in the first embodiment which is shown in Fig. 9.

The transmission optical fiber 40 is coated with a protective coating layer, and the cylindrical ferrule 42 is fitted on a front end of the optical fiber 40. When this ferrule 42 is inserted into the precision sleeve 32, the ferrule 42 prevents the imperfect alignment of the transmission optical fiber 40. The connector 80 is attached on the other end of the transmission optical fiber 40. Another optical fiber is coupled to the connector 80.

On the other hand, the optical reception module 30A has the same configuration as the optical transmission module 30 shown in Fig. 38 except that the optical device 34 is a pin photodiode for receiving light. When the ferrule 42 is inserted into the sleeve 32 of the optical reception module 30A, the optical device 34 receives light emerging from the optical fiber 40A supported by the ferrule 42.

As shown in Fig. 38, the reception optical fiber 40A is coated with a coating layer to be protected. The cylindrical ferrule 42 is fitted on the tip of the reception optical fiber 40A. When this ferrule 42 is inserted into the sleeve 32, the ferrule 42 prevents the imperfect alignment of the reception optical fiber 40A. The connector 80A is attached on the other end of the transmission optical fiber 40A. Another optical fiber is coupled to the connector 80A.

In the present embodiment, the connectors 80 and 80A are attached to the ends of the transmission optical fiber 40 and the reception optical fiber 40A but the connector plugs 41 and 41A shown in Fig. 10 may be attached to the optical fibers 40 and 40A, or the optical connectors 80 and 80A may be omitted.

The housing 101 of the card-shaped optical data link device with the above-described configuration is inserted into the card slot 210 of the personal computer as shown in Fig. 7, and another optical fibers are coupled to the transmission optical fiber 40 and the reception optical fiber 40A with the connectors 80 and 80A when data are transmitted between the computer and the external device in optical communications.

When the data are transmitted from the computer to the external device in optical communications, an electric signal is sent from the computer 200 to the electronic circuit board 20 through the electric

connector 22, and the electronic circuit board 20 processes the electric signal. The processed electric signal is sent to the optical transmission module 30. Then, the optical device 34 such as an LED converts the electric signal into the optical signal, and the optical signal is transmitted to the external device such as another computer through the transmission optical fiber 40.

5 On the other hand, when the data are received from the external device, an optical signal is sent from the external device to the optical transmission module 30A through the reception optical fiber 40A. Then, the optical device 34 such as a pin photodiode of the optical reception module 30A converts the optical signal into the electric signal and the electric signal is sent to the electronic circuit board 20. The electronic circuit board 20 processes the electric signal, and the processed electric signal is sent to the computer
10 through the electric connector 22.

According to the above-described configuration of the card-shaped optical data link device, the housing 101 is formed thin in conformity with the type II communication card standardized by JEIDA, so that the existing card slot of the computer can be used to transmit and receive data in optical communication. Further, the end of the ferrule 42 is fitted hard into the small-diameter portion 13c of the attaching hole 13A,
15 so that a presser for fixing the ferrule 42 is not required and the reduction of the number of parts, the improvement of the work efficiency upon the installation and the cost reduction are attained. The frame 111 is sandwiched between the metal panels 121, so that the electronic circuit board 20, the electric connector 22, the optical transmission module 30 and the optical reception module 30A are efficiently protected and shield from the external environment. The precision sleeves 37 are formed at the sleeves 32 of the optical
20 transmission module 30 and the optical reception module 30A, which largely suppress optical losses.

The existing card slot of the computer or others can be used to transmit and receive data in optical communications with the card-shaped optical data link device in the present embodiment.

The card-shaped optical data link device of the seventh embodiment will be described with reference to Fig. 39 and Fig. 40. The card-shaped optical data link device of the present embodiment belongs to the
25 third type card-shaped optical data link device. The card-shaped optical data link device of the present embodiment is different from the card-shaped optical data link device of the sixth embodiment in that, as shown in Fig. 39, a pair of holding stripes 13d are formed in each attaching hole 13A. The holding stripes 13d hold an MU-optical connector plug 41D supporting a transmission optical fiber 40 or a reception optical fiber 40A as shown in Fig. 40. The MU-optical connector plug 41D has no tab.

30 The optical transmission module 30 and the optical reception module 30A utilized in this embodiment is the same as the ones used in the first embodiment, shown in Fig. 9.

The attaching hole 13A, as shown in Fig. 39, has a small diameter portion 13b to which the optical transmission module 30 or the optical reception module 30A are inserted and which is provided on the short side of the frame 111, a largest diameter portion 13a which is continuously formed with the small diameter
35 portion 13b and to which the sleeve 32 is inserted, and a large diameter portion 13c which is continuously formed with the largest diameter portion 13a. The L-shaped pair of holding stripes 13d for holding the MU-optical connector plug 41D without a tab are formed at the largest diameter portion 13a.

The MU-optical connector plug 41D is formed 3.75mm in thickness and the transmission optical fiber 40 or the reception optical fiber 40A is placed at one end of the MU-optical connector plug 41D. As shown in
40 Fig. 40, a rubber hood 41a is placed on the optical fiber 40 or 40A. The MU-optical connector plug 41D is receptacle type, which is superior in small size, light weight, operability, high reliability, low cost and high performance. The MU-optical transmission connector plug 41D without a tab is used. This is because (1) once the MU-optical transmission connector plug 41D is inserted into the attaching hole 13A, it is never removed therefrom unless some equipment is used because of the tab, and (2) the MU-optical transmission
45 connector plug 41D is able to be inserted into the housing 101 which is formed in conformity with the type II communication card standardized by JEIDA.

The existing card slot of a computer or others can be used to transmit and receive data in optical communications with the card-shaped optical data link device in the present embodiment. The card-shaped optical data link device is directly connected to an optical fiber plug socket placed on a floor.

50 In the above first to seventh embodiments, the optical communication means is a computer but it is apparent that another devices can be used if they can be used in optical communications, for example, facsimiles, measuring apparatus, optical devices, electrical communication device etc.

From the invention thus described, it will be obvious that the invention may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all
55 such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

The basic Japanese Application Nos. 18573/1994 and 18566/1994 both filed on February 15, 1994 are hereby incorporated by reference.

Claims

1. A card-shaped optical data link device comprising:
 - an electric connector for receiving and transmitting an electric signal from and to an external environment;
 - electric signal processor electrically connected to said electric connector;
 - an optical transmission module electrically connected to said electric signal processor, for converting the electric signal received from said electric signal processor into an optical signal;
 - an optical reception module electrically connected to said electric signal processor, for converting an optical signal into an electric signal;
 - an optical connector for supporting said optical transmission module and said optical reception module;
 - a frame for supporting said electric connector and said optical connector at a position opposing to said electric connector; and
 - a pair of panels for sandwiching said frame and constituting an envelope with said frame, said envelope housing said electric connector, said electric signal processor, said optical transmission module, said optical reception module and said optical connector;
 - said electric connector, said electric signal processor, said optical connector, said optical transmission module and said optical reception module being located within said envelope.
2. A card-shaped optical data link device according to claim 1, wherein said optical connector has a division plate to divide an internal space of said optical connector into two holding spaces, a hole in each holding space to which one of said optical transmission module and said optical reception module is inserted, and a pair of holding stripes in each holding space for holding an optical coupling of an optical fiber to be inserted into said holding space with one of said optical transmission module and said optical reception module.
3. A card-shaped optical data link device according to claim 1, wherein said optical connector has cuts on a surface to be covered with said panel.
4. A card-shaped optical data link device according to claim 3, wherein said cuts are formed on both the surfaces of said connector to be covered with said panels.
5. A card-shaped optical data link device according to claim 3, wherein said cuts are formed on one of the surfaces of said connector to be covered with said panels.
6. A card-shaped optical data link device according to claim 1, wherein said frame is an open case having two adapting spaces at opposing sides, for said optical connector and said electric connector.
7. A card-shaped optical data link device according to claim 1, wherein a thickness of said optical connector is substantially equal to a thickness of said frame.
8. A card-shaped optical data link device according to claim 1, wherein said frame and said optical connector are integrally formed from one material.
9. A card-shaped optical data link device according to claim 1 further comprising an optical transmission connector plug including a transmission optical fiber, to be fitted into said holding space of said optical connector so that said transmission optical fiber is optically coupled with said optical transmission module; and an optical reception connector plug including a reception optical fiber, to be fitted into said holding space of said optical connector so that said reception optical fiber is optically coupled with said optical reception module.
10. A card-shaped optical data link device comprising:
 - an electric connector for receiving and transmitting an electric signal from and to an external environment;
 - electric signal processor connected to said electric connector;
 - an output socket electrically connected to said electric signal processor;
 - a frame for supporting said electric connector and said optical connector at a position opposing to

said electric connector;

a pair of panels for sandwiching said frame and constituting an envelope with said frame, said envelope housing said electric connector, said electric signal processor and said output socket;

5 a cable connected to said output socket to transmit an electric signal from and to said electric signal processor;

an optical transmission module for converting the electric signal received from said electric signal processor through said cable into an optical signal;

an optical reception module for converting an optical signal into an electric signal and sending the electric signal to said electric signal processor through said cable;

10 an optical connector for supporting said optical transmission module and said optical reception module; and

a housing for storing said optical connector, said optical transmission module, and said optical reception module.

15 11. A card-shaped optical data link device according to claim 10, wherein said optical connector further comprises a driving circuit board for driving said optical transmission module and said optical reception module.

20 12. A card-shaped optical data link device according to claim 10, wherein said optical connector has a partition plate to divide an internal space of said optical connector into two spaces, a division plate to divide one of said two spaces into two holding spaces, and a pair of holding stripes in each holding space for holding an optical coupling of an optical fiber to be inserted into said holding space with one of said optical transmission module and said optical reception module.

25 13. A card-shaped optical data link device according to claim 10, wherein said optical connector has cuts on a surface lying over said optical transmission module and said optical reception module.

30 14. A card-shaped optical data link device according to claim 13, wherein said cuts are formed on one of the surfaces lying over said optical transmission module and said optical reception module.

30 15. A card-shaped optical data link device according to claim 13, wherein said cuts are formed on both the surfaces lying over said optical transmission module and said optical reception module.

35 16. A card-shaped optical data link device according to claim 10, wherein a thickness of said housing is substantially equal to a thickness of said envelope.

17. A card-shaped optical data link device according to claim 10, wherein said housing and said optical connector are integrally formed from one material.

40 18. A card-shaped optical data link device according to claim 8 or 17, wherein said material is an engineering plastic.

45 19. A card-shaped optical data link device according to claim 1 or 10, wherein said optical connector is made of metal.

20. A card-shaped optical data link device according to claim 1 or 10, wherein said optical connector is made of plastic.

50 21. A card-shaped optical data link device according to claim 10 further comprising an optical transmission connector plug including a transmission optical fiber, to be fitted into said optical connector so that said transmission optical fiber is optically coupled with said optical transmission module; and an optical reception connector plug including a reception optical fiber, to be fitted into said optical connector so that said reception optical fiber is optically coupled with said optical reception module.

55 22. A card-shaped optical data link device according to claim 9 or 21, wherein said optical transmission connector plug and said optical reception connector plug are integrally formed.

23. A card-shaped optical data link device according to claim 9 or 21, wherein said optical transmission connector plug and said optical reception connector plug are MU-type optical connector plugs.

24. A card-shaped optical data link device according to claim 10, wherein said optical connector comprises a first optical connector for supporting said optical transmission module, and a second optical connector for supporting said optical reception module; and

said housing comprises a first housing for storing said first optical connector and said optical transmission module, and a second housing for protecting said second optical connector and said optical reception module.

25. A card-shaped optical data link device according to claim 24, wherein said first optical connector and said second optical connector each has a division plate to divide an internal space of said optical connector into two holding spaces, and a pair of holding stripes for holding an optical coupling of an optical fiber to be inserted into said holding space with one of said optical transmission module and said optical reception module.

26. A card-shaped optical data link device comprising:

an electric connector for receiving and transmitting an electric signal from and to an external environment;

electric signal processor electrically connected to said electric connector;

an optical transmission module electrically connected to said electric signal processor, for converting the electric signal received from said electric signal processor into an optical signal;

an optical reception module electrically connected to said electric signal processor, for converting an optical signal into an electric signal;

a transmission optical fiber having a first end fitted into said optical transmission module;

a reception optical fiber having a first end fitted into said optical reception module;

a frame for supporting said electric connector, and said optical transmission module and said optical reception module at a position opposing to said electric connector; and

a pair of panels for sandwiching said frame and constituting an envelope with said frame, said envelope housing said electric connector, said electric signal processor, said optical transmission module, and said optical reception module;

said electric connector, said electric signal processor, said optical transmission module and said optical reception module being located within said envelope.

27. A card-shaped optical data link device according to claim 26, wherein said frame has a pair of fixing holes for holding said optical transmission module and said optical reception module so as not to be removed from said frame.

28. A card-shaped optical data link device according to claim 27, wherein said first ends of said transmission optical fiber and said reception optical fiber are protected with ferrules; and

said fixing hole has a first portion with a first diameter, a second portion with a second diameter smaller than said first diameter, and a third portion with a third diameter smaller than said second diameter; and

said first portion holds one of said optical transmission module and said optical reception module; and

said second portion holds said ferrule when said ferrule holding one of said transmission optical fiber and said reception optical fiber is inserted into one of said optical transmission module and said optical reception module.

29. A card-shaped optical data link device according to claim 28, wherein said ferrule is unremovable from one of said optical transmission module and said optical reception module.

30. A card-shaped optical data link device according to claim 27, wherein said transmission optical fiber and said reception optical fiber are supported by an optical transmission plug and an optical reception plug, respectively; and

said fixing hole has a pair of holding stripes for holding one of said optical transmission plug and said optical reception plug.

31. A card-shaped optical data link device according to claim 26, wherein connectors are placed at second ends of said transmission optical fiber and said reception optical fiber so that another optical fibers are coupled to said transmission optical fiber and said reception optical fiber with the connectors.

5 32. A card-shaped optical data link device according to claim 26, wherein said frame is an open case having one adapting space for said electric connector.

33. A card-shaped optical data link device according to claim 1, 10 or 26, wherein said frame is made of plastic.

10 34. A card-shaped optical data link device according to claim 1, 10 or 26, wherein said panels are made of metal.

35. A card-shaped optical data link device according to claim 1, 10 or 26, wherein said panel has a bulge.

15 36. A card-shaped optical data link device according to claim 1, 10 or 26, wherein said optical reception module has a cylindrical sleeve to which an optical fiber is inserted and a body having flat parallel surfaces and comprising an optical device.

20 37. A card-shaped optical data link device according to claim 36 when dependent on claim 10 or 26, wherein a thickness of said body of said optical reception module, between said flat surfaces is less than or equal to a thickness of said frame.

25 38. A card-shaped optical data link device according to claim 36 when dependent on claim 1, wherein a thickness of said body of said optical reception module, between said flat surfaces is less than or equal to a thickness of said optical connector.

30 39. A card-shaped optical data link device according to claim 1, 10 or 26, wherein said optical transmission module has a cylindrical sleeve to which an optical fiber is inserted and a body having flat parallel surfaces and comprising an optical device.

40. A card-shaped optical data link device according to claim 39 when dependent on claim 10 or 26, wherein a thickness of said body of said optical transmission module, between said flat surfaces is less than or equal to a thickness of said frame.

35 41. A card-shaped optical data link device according to claim 39 when dependent on claim 1, wherein a thickness of said body of said optical transmission module, between said flat surfaces is less than or equal to a thickness of said optical connector.

40 42. A card-shaped optical data link device according to claim 27, wherein said optical reception module and said optical transmission module are connected to said electric connector with wires.

45

50

55

F i g. 1




Fig. 2




Fig. 3







Fig. 4



F i g. 5



F i g. 6



F i g. 7







Fig. 8




F i g. 9




F i g. 10




F i g. 11




F i g. 12




F i g. 13




F i g. 14




F i g. 15




F i g. 16




F i g. 17



F i g. 18



F i g. 19



F i g. 20




Fig. 21




Fig. 22







Fig. 23




F i g. 24




F i g. 25




F i g. 26




F i g. 27




F i g. 28




F i g. 29




F i g. 30




F i g. 31




F i g. 32




F i g. 33




F i g. 34




F i g. 35



F i g. 36



F i g. 37



F i g. 38




Fig. 39





Fig. 40





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 95 10 2089

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP-A-0 437 161 (IBM) * claim 1 * * column 14, line 32 - line 38 * * figure 1 * ---	1,10,26	G02B6/38
A	EP-A-0 456 298 (DU PONT) * column 3, line 19 - line 29 * * figure 1 * -----	1,10,26	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			G02B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 18 May 1995	Examiner Luck, W
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document	

EPO FORM 1503 01.92 (P04C01)

